

Technical Bulletin

Polymer 600

DESCRIPTION

Polymer 600 is a compounded styrene butadiene copolymer emulsion polymer for use as a non skid carpet and fabric back coating.

The product does not require foaming.

BENEFITS

Polymer 600 has the following beneficial characteristics.

- Very Economical
- Ready to Use
- Non Skid Coating
- Does Not Require Foaming
- Excellent Mechanical Stability

TYPICAL PROPERTIES

Color	Off-White
Texture	Liquid
Solids Content	About 40%
PH	About 9.5
Viscosity	About 7500 CPS
Ionic Nature	Anionic
Specific Gravity	About 1.07

PREPARATION

Polymer 600 should be added to the bath, diluted to the desired concentration and thoroughly mixed.

APPLICATION

Polymer 600 should be applied by kiss roll or blade coating technique.

STORAGE

Polymer 600 should be stored in a cool, dry and well-ventilated area.

HANDLING

Follow good industrial hygiene when handling **Polymer 600**. Please refer to the Material Safety Data Sheet for details.

PACKAGING

Polymer 600 is available in bulk, returnable (or one-way) totes or drums.

Date Established: 11/25/08

Date Revised:

The information contained in this bulletin is to the best of our knowledge, true and accurate. This information is offered as a general guide to facilitate experimentation as to its suitability to the local plant environment, but neither an express or implied warrantee of merchantability of the above mentioned product for particular use. American Textile, LLC make no guarantee of results and assume no obligation or liability whatsoever in connection with this information. This information is neither a license to operate under, nor is it intended to suggest infringement of any patent rights.