

Technical Bulletin

SurfTechs 4060

DESCRIPTION

SurfTechs 4060 is a self cross-linking soft hand high solids hydrophobic acrylic copolymer. The product may be used as a binder for non woven boat cover fabric. It may also be used as a hand builder for home furnishing fabrics where water and UV resistance are desirable. It may be used alone or in conjunction with other chemicals such as flame-retardants, catalysts and resins.

BENEFITS

SurfTechs 4060 has the following beneficial characteristics.

- Economical
- Soft Hand
- Excellent Water Resistance
- UV Stable
- Good Color Acceptance

TYPICAL PROPERTIES

Color	White
Texture	Liquid
Solids Content	About 59%
pH	About 6.5
Viscosity	<500 CPS
Tg	-4°C
PS	300 – 500 nm
MFFT	<0°C

PREPARATION

SurfTechs 4060 should be added to the finish bath, diluted to the desired concentration and thoroughly mixed.

APPLICATION

SurfTechs 4060 may be applied by padding, coating, foaming or spraying techniques.

STORAGE

SurfTechs 4060 should be stored in a cool, dry and well-ventilated area.

HANDLING

Follow good industrial hygiene when handling **SurfTechs 4060**. Please refer to the Material Safety Data Sheet for details.

PACKAGING

SurfTechs 4060 is available in bulk, totes or drums.

Date Established: 08/07/09
Date Revised:

The information contained in this bulletin is to the best of our knowledge, true and accurate. This information is offered as a general guide to facilitate experimentation as to its suitability to the local plant environment, but neither an express or implied warranty of merchantability of the above mentioned product for particular use. American Textile, LLC make no guarantee of results and assume no obligation or liability whatsoever in connection with this information. This information is neither a license to operate under, nor is it intended to suggest infringement of any patent rights.